

**Statistics**

| Description  | Symbol | Avg    | Max    | Min    | Max/Min | Avg/Min |
|--------------|--------|--------|--------|--------|---------|---------|
| Calc Zone #1 | +      | 1.2 fc | 4.7 fc | 0.1 fc | 47.0:1  | 12.0:1  |

**Schedule**

| Symbol | Label | Quantity | Manufacturer       | Catalog Number  | Description  | Lamp        | Number Lamps | Filename                       | Lumens Per Lamp | Light Loss Factor | Wattage |
|--------|-------|----------|--------------------|---|--|-------------|--------------|--------------------------------|-----------------|-------------------|---------|
|        | S3    | 4        | Sternberg Lighting | SL760-FFG-84L45T3R-MDL03 pole mounted at 16' above grade    | Solana Series, Post Top, Flat Frosted Acrylic, Type 3R Optic         | 84 LEDs     | 1            | SL760-FFG-84L45T3R-MDL03.IES   | 6815            | 0.9               | 95.4    |
|        | S3-HS | 24       | Sternberg Lighting | SL760-FFG-84L45T3-MDL03-HSS pole mounted at 16' above grade | SL660 medium size Solana Post Top, Clear Flat Glass (AR) HSS, Type 3 | 84 LED, 45k | 1            | SL660-FG-84L45T3-MDL03-HSS.IES | 7179            | 0.9               | 92      |
|        | S4-HS | 4        | Sternberg Lighting | SL760-FFG-84L45T4-MDL03-HSS pole mounted at 16' above grade | SL660 medium size Solana Post Top, Clear Flat Glass (AR) HSS, Type 4 | 84 LED, 45k | 1            | SL660-FG-84L45T4-MDL03-HSS.IES | 7673            | 0.9               | 92.3    |