


Statistics

Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Calc Zone #1	+	1.5 fc	7.5 fc	0.1 fc	75.0:1	15.0:1

Plan View

Scale - 1" = 60ft

Schedule

Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage
□	S3	4	Industrial Lighting Products Inc	AL-70WLED-UNIV-40-T3 pole mounted at 16' above grade	Grey die cast aluminum housing, clear type III optics	48 white LEDs, two boards with 24 LEDs each	1	AL-70WLED-UNIV-40-T3-IES.ies	8367	0.9	70.74
□	S3-HS	21	Industrial Lighting Products Inc	AL-70WLED-UNIV-40-T3-HSS pole mounted at 16' above grade	Grey die cast aluminum housing, clear type III optics	48 white LEDs, two boards with 24 LEDs each	1	AL-70WLED-UNIV-40-T3-IES.ies	8367	0.9	70.74
□	S4-2	1	Industrial Lighting Products Inc	AL-70WLED-UNIV-40-T4 pole mounted at 16' above grade	Grey die cast aluminum housing, clear type IV optics	48 white LEDs, two boards with 24 LEDs each	1	AL-70WLED-UNIV-40-T4-IES.ies	7968	0.9	140.98
□	S4-HS	4	Industrial Lighting Products Inc	AL-70WLED-UNIV-40-T4-HSS pole mounted at 16' above grade	Grey die cast aluminum housing, clear type IV optics	48 white LEDs, two boards with 24 LEDs each	1	AL-70WLED-UNIV-40-T4-IES.ies	7968	0.9	70.49